

Linksys PAP2

VoiceDirector users can utilize the Linksys PAP2 to place low-cost VoIP calls all over the world

VoiceDirector Solution

With the Linksys PAP2, businesses can save by enabling employees to make low-cost calls from headquarters and home/satellite offices. The PAP2 is compatible with the VoiceDirector corporate calling solution and can be easily and economically implemented at any location on the VoiceDirector network.



Easy to Implement

In order to get started, simply:

- Attach standard phone(s) to the Linksys PAP2
- Connect the PAP2 to a broadband router or gateway
- Configure the PAP2 via the easy-to-use Web interface

Hardware Specifications

Ports	<ul style="list-style-type: none"> • One 10/100 RJ-45 network port • Two standard RJ-11 phone ports
Standards	IEEE 802.3 (10BaseT), IEEE 802.3u (100BaseTX)
Power Input	5V DC 2.0A
Certifications	<ul style="list-style-type: none"> • FCC • cUL • CE

Standards and Protocols

Audio Codecs	Include G.711 and G.729a
Voice Protocol	SIP v2

Physical Specifications

Dimensions	101 mm x 101 mm x 15 mm (3.98" x 3.98" x 0.59")
Weight	0.14 kg (4.8 oz.)
Operational Temperature	5° to 45° C (41° to 113° F)
Storage Temperature	-25° to 85° C (-13° to 185° F)
Operating Humidity	10% to 90% (non-condensing)
Storage Humidity	5% to 90% (non-condensing)

For more information on VoiceDirector, please visit www.voicedirector.net