

LIP-6812/6830

The LIP-6812 and LIP-6830 VoIP phones enable broadband users to place low-cost calls all over the world

In addition, these VoIP phones are completely compatible with the VoiceDirector corporate calling solution

VoiceDirector Solution

The LIP-6812 and LIP-6830 are perfect complements to the VoiceDirector corporate calling solution, enabling employees to make low-cost calls from headquarters and home/satellite offices.

These VoIP phones can be easily implemented at any location on the VoiceDirector network and provide a familiar calling experience, facilitating a rapid deployment and return on investment (ROI).

Corporate Calling Features

In addition to a full duplex speakerphone, the LIP-6812/6830 includes a complete complement of value-added calling features:

- Speed dial
- Caller ID and anonymous call blocking
- Call transfer/forwarding
- Call hold/mute
- Redial
- Do not disturb
- Call return
- Visual message waiting indicator
- Console phone functionality (up to 11 (LIP-6812) / 24 (LIP-6830) lines)
- Headset jack
- PC port (hub)
- PoE (Power over Ethernet)



LIP-6812



LIP-6830

LIP-6812/6830 Specifications

Hardware Specifications

Network Interface	Two RJ-45 connections compatible with IEEE 802.3 10 Base-T
LED Indicators	Message, speaker, mute, line activity
Programmable Buttons	11 (LIP-6812), 24 (LIP-6830)
AC/DC Adapter	Output: 48VDC, 100mA AC/DC adapter Input: 120VAC, 0.1A (max), 60 Hz, 11W (max)

Standards and Protocols

Audio Codecs	G.711, G.729a
Protocols	SIP, TCP/IP, UDP, DHCP, Telnet, TFTP, NTP, RTP

Physical Specifications

Dimensions (H x W x D)	108mm x 203mm x 190mm (LIP-6812) 108mm x 257mm x 190mm (LIP-6830)
Weight	880g (LIP-6812), 1020g (LIP-6830)
Operational Temperature	0° to 40° C
Storage Temperature	-20° to 60° C
Humidity	10% to 85% RH (non-condensing)

*For more information on VoiceDirector, please visit
www.voicedirector.net*