

# Linksys SPA941

## The Linksys SPA941 IP phone enables VoiceDirector customers to place low-cost calls all over the world

### VoiceDirector Compatible

The Linksys SPA941 provides corporate customers with a multiple line VoIP calling solution. This IP phone can be easily implemented at any location on the VoiceDirector network, enabling employees to make low-cost calls from headquarters and home/satellite offices.

### Corporate Calling Features

The Linksys SPA941 delivers a complete set of business class calling features, including:

- Speakerphone
- Caller waiting
- Call blocking (anonymous and selective)
- Caller ID name and number (plus outbound Caller ID blocking)
- Do not disturb
- Subsequent incoming calls with calling name and number
- Multiple ring tones with selectable ring tone per line



# Linksys SPA941 Specifications

## *Hardware Specifications*

<b>Network Interface</b>	One 10/100 Base-T Ethernet port for WAN interface
<b>LED Indicators</b>	Four call appearance/line buttons with associated tri-color LED, line LED state indication (active, idle, on hold, unregistered), speakerphone on/off button with LED, headset on/off button with LED, mute button with LED, message waiting indicator with LED, voicemail message retrieval button, hold button, LED test function
<b>Adapter</b>	12-Volt DC adaptor

## *Standards*

<b>Speech Codec Capabilities</b>	G.711 (A-law and u-law), G.726 (16/24/32/40 Kbps), G.729a, G.723.1 (6.3 kbps, 5.3 kbps)
<b>Regulatory Approvals</b>	FCC (Part 15, Class B), CE, A-Tick, ICES-003

## *Physical Specifications*

<b>Dimensions (H x W x D)</b>	6.3" x 7.68" x 7.09"
<b>Operational Temperature</b>	41° to 113° F (5° to 45° C)
<b>Storage Temperature</b>	-13° to 185° F (-25° to 85° C)
<b>Humidity</b>	10% to 90% (non-condensing)

*For more information, please visit [www.voicedirector.net](http://www.voicedirector.net)*